



| PART# | DESCRIPTION | MAIN MATERIAL / NOTE | ASTM, AISI CODE | RELATED DIN CODE | QTY |
|-------|----------------------|-------------------------------------|-----------------|------------------|-----|
| 1 | Power Cable | PVC Sheath AWG16/3-16ft | | | 1 |
| 20 | Pump Casing | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 21 | Impeller | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 23 | Suction Strainer | Steel (Cold Rolled) | A109/A1008 | EN 10130 | 1 |
| 25 | Mechanical Seal | Silicon Carbide / W-14HC | | | 1 |
| 26 | Oil Seal | Nitrile Butadiene Rubber / SC-15287 | | | 1 |
| 29 | Oil Casing | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 32 | Discharge Connection | Cast Iron / NPT 4" | A48M Class30B | EN 1561 GJL-200 | 1 |
| 35 | Oil Plug | Stainless Steel | S 30400 | 1.4301 | 1 |
| 36 | Lubricant | White Mineral Oil ISO VG32 | | | |
| 49 | Bottom Plate | Steel (Cold Rolled) | A109/A1008 | EN 10130 | 1 |
| 51A | Motor Head Cover | Aluminium Alloy Die Casting | B85 383.0 | EN 1706 AC-46100 | 1 |
| 51B | Pump Head Cover | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 52A | Upper Bearing | #6201ZZC3 | | | 1 |
| 52B | Lower Bearing | #6202ZZC3 | | | 1 |
| 53 | Motor Protector | | | | 1 |
| 54 | Shaft | Stainless Steel | S 40300 | 1.4000 | 1 |
| 55 | Rotor | | | | 1 |
| 56 | Stator | | | | 1 |
| 60 | Bearing Housing | Cast Iron | A48M Class25B | EN 1561 GJL-150 | 1 |
| 64 | Motor Housing | Steel (Cold Rolled) | A109/A1008 | EN 10130 | 1 |
| 65 | Outer Cover | Stainless Steel | S 30400 | 1.4301 | 1 |
| 68 | Handle | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 2 |
| 71 | Shaft Sleeve | Stainless Steel | S 40300 | 1.4000 | 1 |
| 76 | Capacitor | | | | 1 |
| 77 | Centrifugal Switch | | | | 1 |