



TSURUMI PUMP

MODEL

50PSF2.75S-61

Parts List		Effluent Pumps		Control No:		
ITEM	PARTS No.	DESCRIPTION	Q'TY	SIZE	MATERIAL	NOTES
1	001-471-12	Power Cable 32'-110V	1	LB, AWG14/3 x 32' (w/ CSA3P)	VCT	
1	001-952-12	Power Cable 32'-220V	1	TLB, AWG16/3 x 32', 316-Gland	VCT	see 001-466-14/-943-23 w/o Plug
1	001-471-25	Power Cable 50'-110V-Option	1	LB, AWG14/3 x 50' (w/ CSA3P)	VCT	
2	143-146-18	Tapping Screw	2	M5x20 (Pan), w/ Washer, Sprit	SUS304	
3	003-100-13	Gland	1	LB	SUS304	c/w Power Cable
4	051-224-13	Motor Head Cover	1	3/4/8-PU(T)	Resin	
5	141-029-18	Acorn Nut	4	M6	SUS304	
6	142-126-19	Washer	4	M6	SUS304	
7	127-200-11	Retainer (Capacitor)	1	3/4/8-PU(A/W)	SECC	
8	143-153-18	Tapping Screw	2	M3.5x8 (Truss)	SWCH	
9	076-136-14	Capacitor 110/115/120V-60HZ	1	SH-JPX , 43MFD-220VAC		
9	076-137-15	Capacitor 220V-60HZ	1	SH-JPX , 12MFD-450VAC		
10	053-000-08	Motor Protector 110/115/120V-60HZ	1	KA142-BDXL14F (T+H)		
10	053-000-34	Motor Protector 220V-60HZ	1	KA142-BPXL06D (T+H)		
11	143-138-17	Tapping Screw	2	M4x12 (Truss)	SWRM	
12	143-150-15	Pan Screw	4	M5x168 (20L)	SWRM	
13	142-112-25	Washer	4	M5 (N, D=10)	SPC	see 142-112-12
14	121-472-18	Gasket (H.Cover/H.C.Spacer)	1	P.C.125xd130x2.3t	NR	*
15	082-102-10	Head Cover Spacer	1	3/4/8-PU(A/W)(T)	Resin	
16	121-471-17	Gasket (H.C.Spacer/M.Frame)	1	d126.6xD135.6x6t	NR	*
17	050-411-16	Motor Bracket	1	3/4/8-PU(A/W)(T)	SPC	
18	009-187-12	Grounding Wire	1	AWG16 x 150L		
18	009-190-18	Grounding Wire	1	AWG16 x 150L , G/Y		
19	143-085-34	Pan Screw	1	M4x6, w/ S.Washer	BSBM	see 143-085-21
20	056-	Stator 220V-60HZ	1	8-PU(A/W) (220/230-50, 220-60)		
21	071-325-17	Collar	1	54L	SECC	
22	142-192-16	Wave Washer	1	#6201 (T=0.4)	SK-5	
23	052-100-15	Ball Bearing (Upper)	1	6201ZZC3		
24	055-000-22	Rotor and Shaft	1	8-PU(A/W)		c/w Ball Bearings
25	061-157-15	Bearing Collar	1	d15.1xD21x1.6t	SPC	
26	052-152-12	Ball Bearing (Lower)	1	6302ZZC3		
27	060-399-18	Bearing Housing	1	8-PU(T)	ADC	
28	025-290-19	Mechanical Seal	1	W-14HL	SiC+CCBN	
29	121-464-17	Gasket (M.Frame/O.Casing)	1	3/4/8-PU(T)	NBR	*
30	035-127-15	Oil Plug	1	M10x15 (Binding Screw)	SUS304	
31	121-246-11	Gasket (Oil Plug)	1	d10.3xD16x2t	PE-sheet	*
32	140-435-18	Bolt	4	M6x30, w/ Washer	SUS304	
33	029-300-15	Oil Casing	1	3/4/8-PU	Resin	
34	143-139-18	Truss Screw	4	M6x40, w/ PE-Washer	SUS304	
35	142-354-18	Conical Spring Washer	1	d11.2xD22.5x0.8t	SUS304	
36	021-G33-29	Impeller (60Hz)	1	8-PSHT-60Hz	Resin	60Hz
36	021-G34-20	Impeller (50Hz)	1	8-PSHT-50Hz	Resin	50Hz
37	143-140-12	Truss Screw	1	M6x12, w/ Washer	SUS304	
38	122-452-15	O-Ring (O.Casing/U.P.Casing)	1	130xd2.8	NBR	*
39	020-908-12	Upper Pump Casing	1	3/4/8-PU/PN/PSH, Upp.	Resin	
40	203-065-11	Ball (Air Valve)	1	d17	Glass	
41	121-465-21	Gasket (U./L. P.Casing)	1	3/4/8-PU(T) (Gray)	NBR	* NEW
41	121-465-18	Gasket (U./L. P.Casing)	1	3/4/8-PU(T)	NBR	* OLD
42	020-909-13	Lower Pump Casing	1	3/4/8-PN/PSH/TM, Low.	Resin	
43	023-445-15	Strainer Stand	1	3/4/8-PN/PSH/TM	Resin	
44	143-141-13	Pan Screw	6	M6x80, w/ Washer	SUS304	
45	140-436-19	Bolt	2	M8x55, w/ Washer	SUS304	
46	048-274-18	Companion Flange 2" NPT	1	NPT-2" (P.C.90)	Resin	
47	121-469-12	Gasket (Companion Flange)	1	P.C.90xd58x2t	NR	*
48	141-121-11	Nut	2	M8 (S=12)	SUS304	
<Gasket O-Ring Set>						
	173-501-18	Gasket O-Ring Set	1set	(*)		
14	121-472-18	Gasket (H.Cover/H.C.Spacer)	1	P.C.125xd130x2.3t	NR	*
16	121-471-17	Gasket (H.C.Spacer/M.Frame)	1	d126.6xD135.6x6t	NR	*
29	121-464-17	Gasket (M.Frame/O.Casing)	1	3/4/8-PU(T)	NBR	*
31	121-246-11	Gasket (Oil Plug)	1	d10.3xD16x2t	PE-sheet	*
38	122-452-15	O-Ring (O.Casing/U.P.Casing)	1	130xd2.8	NBR	*
41	121-465-21	Gasket (U./L. P.Casing)	1	3/4/8-PU(T) (Gray)	NBR	* NEW
41	121-465-18	Gasket (U./L. P.Casing)	1	3/4/8-PU(T)	NBR	* OLD
47	121-469-12	Gasket (Companion Flange)	1	P.C.90xd58x2t	NR	*
		Lubricant		Turbine Oil#32 250 mL (8.5 floz)	(SAE 10W-20)	

* Indicates items included in set



TSURUMI PUMP

MODEL

50PSF2.75S-61

Parts List		Effluent Pumps		Control No:		
ITEM	PARTS No.	DESCRIPTION	Q'TY	SIZE	MATERIAL	NOTES
		Parts for guide rail fittings are shown in the following Control No.				
		TOK3-P (TOK3-3-1-1)				

